

AT-44



with PTFE super power silicone-free

Thanks to its special formula and very low friction coefficient, WEICON AT-44 combines corrosion protection, cleaning, water displacement, lubrication and conservation in a single product.

WEICON AT-44 loosens seized threads, bolts, fittings and valves, dispels moisture from electrical cables, prevents tracking currents and makes it easier to start wet motors. It eliminates squeaky and creaky noises on hinges, guides, bearings and all types of joints and couplings.

It eliminates squeaky and creaky noises on hinges, guides, bearings and all types of joints and couplings. It cleans soiled surfaces and leaves a razor-thin film which doesn't smear or stick and does not attract dust. It protects and preserves all types of tools, machines, and electrical and mechanical precision devices and keeps them functional.

AT-44 knows almost no limitations in workshop, automotive, shipping, electrical, agricultural, household and hobby applications.

Safety and health

When using WEICON products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes:

| | |
|----------|------------|
| 15250001 | AT-44 1 L |
| 15250005 | AT-44 5 L |
| 15250010 | AT-44 10 L |
| 15250028 | AT-44 28 L |

Accessories:

| | |
|----------|--------------------------------------|
| 15810001 | Adapter for WSD 400, |
| 15811002 | Spray-Valve set for WSD 400, |
| 15811400 | Pressurized-Air Spray Can WSD 400, |
| 15830001 | Adjusting Valve for cans, 5 L & 10 L |
| 15831001 | Adjusting Valve for cans, 28 L |
| 15841500 | Pump-Dispenser WPS 1500, 1,5 L |
| 15841501 | Extension for WPS 1500, |
| 15843001 | Pump Dispenser Special, |

Technical Data

| | |
|---|--|
| Odour | vanilla |
| Storage stability | 24 months |
| Features | high-performance lubricating oil - with PTFE |
| Colour | yellowish |
| Kinematic viscosity (DIN 51562) at +40°C | 21 mm ² /s |
| Kinematic viscosity (DIN 51562) at +100°C | 4 mm ² /s |
| Temperature resistance | -50 to +210 °C |
| Suitable for application with | WSD 400 and WPS 1500 |
| IMPA-Code | 551599/600/621 |

Storage

Keep in closed original container. Protect from direct sun light. Storage temperature may not exceed +50°C. Store container in a cool, dry and ventilated place.

Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON GmbH & Co. KG
(Headquarters)
Germany
phone +49 (0) 251 9322 0
info@weicon.de
www.weicon.de

WEICON Middle East L.L.C.
United Arab Emirates
phone +971 4 880 25 05
info@weicon.ae
www.weicon.ae

WEICON Inc.
Canada
phone +1 877 620 8889
info@weicon.ca
www.weicon.ca

WEICON Kimya Sanayi Tic. Ltd. Şti.
Turkey
phone +90 (0) 212 465 33 65
info@weicon.com.tr
www.weicon.com.tr

DANLUBE A/S
Tune Parkvej 5
DK-4030 Tune
Denmark
+45 70 25 12 80
info@danlube.dk
www.danlube.dk

WEICON SA (Pty) Ltd
South Africa
phone +27 (0) 21 709 0088
info@weicon.co.za
www.weicon.co.za

WEICON South East Asia Pte Ltd
Singapore
phone (+65) 6710 7671
info@weicon.com.sg
www.weicon.com.sg

WEICON Czech Republic s.r.o.
Czech Republic
phone +42 (0) 417 533 013
info@weicon.cz
www.weicon.cz

WEICON Ibérica S.L.
Spain
phone +34 (0) 914 7997 34
info@weicon.es
www.weicon.es