

## **Technical Datasheet**

Create Date: 17.09.2020 - Seite1/1



# Pneuma-Lube



### Lubricant for pneumatic equipment, high content of PTFE

As a lubricating and corrosion protection agent, this product is the universal problemsolver for all moving parts in pneumatic equipment and accessories. Its special product formula with a high content of PTFE makes it a multi-purpose product for: lubrication, corrosion protection, cleaning, water displacing and conservation.

Pneuma-Lub not only serves in installation or maintenance of pneumatic equipment and accessories but also can be used on pneumatic tools in operation. The excellent weathering resistance allows the use also in other sectors, e.g. in the on and offshore industry. The temperature resistance of the spray ranges from -50°C to +210°C.

## **Technical Data**

Odour	vanilla
Storage stability	24 months
Features	high-performance lubricating oil - with PTFE
Colour	yellowish
Kinematic viscosity (DIN 51562) at +40°C	21 mm²/s
Kinematic viscosity (DIN 51562) at +100°C	4 mm²/s
Temperature resistance	-50 to +210 °C
Suitable for application with	WSD 400 and WPS 1500

## Storage

Keep in closed original container. Protect from direct sun light. Storage temperature may not exceed +50°C. Store container in a cool, dry and ventilated place.

### Safety and health

When using WEICON products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

## Available sizes:

15260001 Pneuma-Lube 1 L 15260005 Pneuma-Lube 5 L 15260010 Pneuma-Lube 10 L 15260028 Pneuma-Lube 28 L

#### Accessories:

 15810001
 Adapter for WSD 400,

 15811002
 Spray-Valve set for WSD 400,

 15811400
 Pressurized-Air Spray Can WSD 400,

 15830001
 Adjusting Valve for cans, 5 L & 10 L

 15841500
 Pump-Dispenser WPS 1500, 1,5 L

 15841501
 Extension for WPS 1500,

 15842001
 Pump Dispenser,

### Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, one adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON GmbH & Co. KG (Headquarters) Germany phone +49 (0) 251 9322 0 info@weicon.de www.weicon.de

WEICON SA (Pty) Ltd South Africa phone +27 (0) 21 709 0088 info@weicon.co.za WEICON Middle East L.L.C. United Arab Emirates phone +971 4 880 25 05 info@weicon.ae www.weicon.ae

WEICON South East Asia Pte Ltd Singapore phone (+65) 6710 7671 info@weicon.com.sg www.weicon.com.sg WEICON Inc. Canada phone +1 877 620 8889 info@weicon.ca www.weicon.ca

WEICON Czech Republic s.r.o. Czech Republic phone +42 (0) 417 533 013 info@weicon.cz www.weicon.cz WEICON Kimya Sanayi Tic. Ltd. Şti. Turkey phone +90 (0) 212 465 33 65 info@weicon.com.tr www.weicon.com.tr

WEICON Ibérica S.L. Spain phone +34 (0) 914 7997 34 info@weicon.es www.weicon.es **DANLUBE A/S** 

Tune Parkvej 5 DK-4030 Tune Denmark +45 70 25 12 80 info@danlube.dk www.danlube.dk